

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 17/07/2017 Revision date: :

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

: Mixture

1.1. Product identifier

Product form	
Product name	
Product code	
Product group	

: Custom Low VPH Mix : AL0-130131

: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Industrial/Professional use spec : Laboratory use: Industrial For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Phenova 6390 Joyce Dr. Suite 100 80403 Golden, CO - United States T 1-866-942-2978 - F 1-866-283-0269 info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number

: ChemTel Assistance (US/Canada) 1-800-255-3924 ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Muta. 1B	H340
Carc. 1A	H350
STOT SE 1	H370
Aquatic Chronic 3	H412

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45 Muta.Cat.2; R46 F+; R12 T; R23/24/25 T; R39/23/24/25 R52/53 Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements	
Labelling according to Regulation (EC)	No. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS06 GHS08
Signal word (CLP)	: Danger
Hazardous ingredients	: benzene; methanol
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapour H301+H311 - Toxic if swallowed or in contact with skin H340 - May cause genetic defects H350 - May cause cancer H370 - Causes damage to organs H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P260 - Do not breathe dust/fume/gas/mist/vapours/spray P270 - Do not eat, drink or smoke when using this product P273 - Avoid release to the environment P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water P308+P313 - IF exposed or concerned: Get medical advice/attention P361+P364 - Take off immediately all contaminated clothing and wash it before reuse P403+P235 - Store in a well-ventilated place. Keep cool P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methanol (Component)	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	97.4	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
benzene (Component)	(CAS-No.) 71-43-2 (EC-No.) 200-753-7 (EC Index-No.) 601-020-00-8	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
ethylbenzene (Component) substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	0.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
hexane (Component)	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
tert-Butyl Methyl Ether (MTBE) (Component) substance with a Community workplace exposure limit	(CAS-No.) 1634-04-4 (EC-No.) 216-653-1 (EC Index-No.) 603-181-00-X	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
n-pentane (Component)	(CAS-No.) 109-66-0 (EC-No.) 203-692-4 (EC Index-No.) 601-006-00-1	0.2	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	
styrene (Component)	(CAS-No.) 100-42-5 (EC-No.) 202-851-5 (EC Index-No.) 601-026-00-0	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372	
toluene (Component)	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	
1,2,4-trimethylbenzene (Component)	(CAS-No.) 95-63-6 (EC-No.) 202-436-9 (EC Index-No.) 601-043-00-3	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	
m-xylene (Component) substance with a Community workplace exposure limit	(CAS-No.) 108-38-3 (EC-No.) 203-576-3 (EC Index-No.) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315	
o-xylene (Component) substance with a Community workplace exposure limit	(CAS-No.) 95-47-6 (EC-No.) 202-422-2 (EC Index-No.) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315	
p-xylene (Component) substance with a Community workplace exposure limit	(CAS-No.) 106-42-3 (EC-No.) 203-396-5 (EC Index-No.) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315	
octane	(CAS-No.) 111-65-9 (EC-No.) 203-892-1 (EC Index-No.) 601-009-00-8	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Name	Product identifier	Specific	Specific concentration limits	
methanol (Component)	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	(3 = <c 10)="" 2,="" <="" h371<br="" se="" stot="">(C >= 10) STOT SE 1, H370</c>		
hexane (Component)	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	(C >= 5) STOT RE 2, H373		

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
4.3. Indication of any immediate medic	al attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the st	ubstance or mixture

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907	/2006 (REACH) with its	amendment Regulation (EU) 2015/830	
5.3. Advice for firefighters	s		
Firefighting instructions		Use water spray or fog for cooling exp chemical fire. Prevent fire fighting wat	posed containers. Exercise caution when fighting any ter from entering the environment.
Protection during firefighting	:	Do not enter fire area without proper	protective equipment, including respiratory protection.
SECTION 6: Accidental r	elease measure	es	
6.1. Personal precautions	s, protective equipm	ent and emergency procedures	
6.1.1. For non-emergency p	personnel		
Emergency procedures	:	Evacuate unnecessary personnel.	
6.1.2. For emergency respo	onders		
Protective equipment	:	Equip cleanup crew with proper prote	ection.
Emergency procedures	:	Ventilate area.	
6.2. Environmental preca	utions		
Prevent entry to sewers and pub	lic waters. Notify auth	norities if liquid enters sewers or public	c waters.
6.3. Methods and materia	l for containment ar	nd cleaning up	
Methods for cleaning up	:	Take up in absorbent material. Collect	st spillage.
6.4. Reference to other se	ections		
See Heading 8. Exposure contro	ls and personal prote	ection.	
SECTION 7: Handling an	d storage		
7.1. Precautions for safe	handling		
Precautions for safe handling	:	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.	
Hygiene measures	:	: Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.	
7.2. Conditions for safe s	torage, including ar	ny incompatibilities	
Storage conditions		: Keep container closed when not in use. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.	
Incompatible materials	:	Direct sunlight.	
7.3. Specific end use(s)			
No additional information availab	le		
SECTION 8: Exposure co	ontrols/persona	I protection	
8.1. Control parameters			
benzene (71-43-2)			
USA OSHA	OSHA PEL (TWA)) (ppm)	10 ppm
USA OSHA	OSHA PEL (Ceilin	g) (ppm)	25 ppm
8.2. Exposure controls			
Appropriate engineering control		Either local exhaust or general room	
Personal protective equipment	:	glasses.	ves. Protective clothing. Protective goggles. Safety
Hand protection	:	Wear chemically resistant protective openetration.	gloves. Wear suitable gloves resistant to chemical
Eye protection	:	Chemical goggles or safety glasses.	Safety glasses.
Oblight and the short market shirts		Manage and a second and the second a	he and an annual to annual annual an annual the desire

		contact.		
_				

- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

	o. i nysicai and chemicai properties
9.1. In	ormation on basic physical and chemical properties
Physical st	ate : Liquid

: Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin

Skin and body protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colour	: Colourless.
Odour	: characteristic.
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Relative density	: No data available
Solubility	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTI	ON 10: Stability and reactivity
10.1.	Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

o additional information available	
ECTION 11: Toxicological info	brmation
.1. Information on toxicological	effects
cute toxicity	: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin.
Custom Low VPH Mix	
ATE CLP (oral)	102.6694045175 mg/kg bodyweight
ATE CLP (dermal)	308.0082135524 mg/kg bodyweight
benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
ATE CLP (gases)	13700 ppmv/4h
ATE CLP (vapours)	43.767 mg/l/4h
ATE CLP (dust,mist)	43.767 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	3500 mg/kg bodyweight
ATE CLP (dermal)	15415 mg/kg bodyweight
ATE CLP (gases)	4000 ppmv/4h

ATE CLP (vapours)

ATE CLP (dust,mist)

17.8 mg/l/4h

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

hexane (110-54-3)	
LD50 oral rat	16000 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3350 mg/kg bodyweight (Rabbit; Read-across; Equivalent or similar to OECD 402)
ATE CLP (oral)	16000 mg/kg bodyweight
tert-Butyl Methyl Ether (MTBE) (1634-04	4-4)
LD50 oral rat	4000 mg/kg (Rat)
LD50 dermal rat	> 6800 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	23576 ppm/4h (Rat)
ATE CLP (oral)	4000 mg/kg bodyweight
ATE CLP (gases)	23576 ppmv/4h
ATE CLP (vapours)	85 mg/l/4h
ATE CLP (dust, mist)	85 mg/l/4h
n-pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
styrene (100-42-5)	
LD50 oral rat	5000 mg/kg (Rat; Literature study; >6000 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rat	2820 mg/kg (Rat; Literature study; OECD 402: Acute Dermal Toxicity; >2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	5010 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	12 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	2770 ppm/4h (Rat; Literature study)
ATE CLP (oral)	5000 mg/kg bodyweight
ATE CLP (dermal)	2820 mg/kg bodyweight
ATE CLP (gases)	2770 ppmv/4h
ATE CLP (vapours)	12 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat; Literature study)
ATE CLP (dermal)	12223 mg/kg bodyweight
	·
1,2,4-trimethylbenzene (95-63-6) LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight;
	Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	18 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
m-xylene (108-38-3)	
LD50 oral rat	5011 - 6630 mg/kg (Rat)
ATE CLP (oral)	5011 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
o-xylene (95-47-6)	
LD50 oral rat	3608 mg/kg (Rat)
ATE CLP (oral)	3608 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
p-xylene (106-42-3)	
LD50 oral rat	4030 mg/kg (Rat)
17/07/2017	EN (English) 6/14

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n valence (400, 42, 2)	
p-xylene (106-42-3)	20 mg/l/4b (Dot)
LC50 inhalation rat (mg/l)	20 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	4740 ppm/4h (Rat)
ATE CLP (oral)	4030 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	4740 ppmv/4h
ATE CLP (vapours)	20 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	100 mg/kg bodyweight
ATE CLP (dermal)	300 mg/kg bodyweight
ATE CLP (gases)	700 ppmv/4h
ATE CLP (vapours)	3 mg/l/4h
ATE CLP (dust,mist)	0.5 mg/l/4h
octane (111-65-9)	
LD50 oral rat	5630 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Rabbit; Read-across; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	118 mg/l/4h (Rat; Literature study)
ATE CLP (oral)	5630 mg/kg bodyweight
ATE CLP (vapours)	118 mg/l/4h
ATE CLP (dust,mist)	118 mg/l/4h
Skin corrosion/irritation	: Not classified
	Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
	Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
, ,	Based on available data, the classification criteria are not met
Germ cell mutagenicity	: May cause genetic defects.
2 - · · · · · · · · · · · · · · · · · ·	Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer.
	Based on available data, the classification criteria are not met
	May cause cancer
Paproductive toxicity	: Not classified
Reproductive toxicity	
	Based on available data, the classification criteria are not met
STOT-single exposure	: Causes damage to organs.
	Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
	Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
	Based on available data, the classification criteria are not met
Potential adverse human health effects and	: Based on available data, the classification criteria are not met.
symptoms	. במסכע סו עימומטוכ עמנמ, גויכ סומססווטמנוסוז סוונכוומ מוכ ווטג וווכג.
· · ···-	

SECTION 12: Ecological information

12.1. Toxicity

benzene (71-43-2)		
LC50 fish 1	5.3 mg/l (LC50; 96 h; Salmo gairdneri)	
EC50 Daphnia 2	10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)	
Threshold limit algae 1	100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)	
ethylbenzene (100-41-4)		
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)	
17/07/2017	EN (English) 7	7/14

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

hexane (110-54-3)	
LC50 fish 1	2.5 mg/l (LC50; 96 h)
EC50 Daphnia 1	2.1 mg/l (EC50; 48 h)
Threshold limit algae 2	26 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system)
tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
LC50 fish 1	672 - 706 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 1	651 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
1,2,4-trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)
m-xylene (108-38-3)	
EC50 Daphnia 1	4.7 mg/l (EC50; 48 h)
LC50 fish 2	8.4 mg/l (LC50; 96 h)
o-xylene (95-47-6)	
EC50 other aquatic organisms 1	4.7 mg/l (72 h; Selenastrum capricornutum; Growth)
LC50 fish 2	8.05 mg/l (LC50; 96 h)
EC50 Daphnia 2	3.2 mg/l (EC50; 48 h)
p-xylene (106-42-3)	
LC50 fish 1	2.6 mg/l (LC50; 96 h)
EC50 Daphnia 2	1.4 mg/l (EC50; 48 h)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)
octane (111-65-9)	
EC50 Daphnia 1	0.38 mg/l (EC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability		
Custom Low VPH Mix		
Persistence and degradability	Not established.	
benzene (71-43-2)		
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.	
Biochemical oxygen demand (BOD)	2.18 g O /g substance	
Chemical oxygen demand (COD)	2.15 g O□ /g substance	
ThOD	3.1 g O□ /gsubstance	
BOD (% of ThOD)	0.7	
ethylbenzene (100-41-4)	ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.	
Biochemical oxygen demand (BOD)	1.44 g O□ /g substance (20d.)	
Chemical oxygen demand (COD)	2.1 g O□ /g substance	
ThOD	3.17 g O□ /g substance	
BOD (% of ThOD)	45.4 (20 days)	
hexane (110-54-3)		
Persistence and degradability	Readily biodegradable in water. Photooxidation in water. easily degradable in the soil.	
ThOD	3.52 g O□ /g substance	
BOD (% of ThOD)	0.63 (Literature study)	
tert-Butyl Methyl Ether (MTBE) (1634-04-4)		
Persistence and degradability	Not readily biodegradable in water.	
n-pentane (109-66-0)		
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil.	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

styrene (100-42-5) Persistence and degradability	Readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in
	soil. Photodegradation in the air.
Chemical oxygen demand (COD)	2.8 g O□ /g substance
ThOD	3.07 g O□ /g substance
BOD (% of ThOD)	0.42
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.
Biochemical oxygen demand (BOD)	2.15 g O□ /g substance
Chemical oxygen demand (COD)	2.52 g O□ /g substance
	3.13 g O□ /g substance
BOD (% of ThOD)	0.69
1,2,4-trimethylbenzene (95-63-6)	Netword's birds models is used a Fermion and in such is used a Dirds models in the soll
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O□ /g substance
m-xylene (108-38-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air. Photooxidat in the air.
Biochemical oxygen demand (BOD)	2.53 g O□ /g substance
Chemical oxygen demand (COD)	2.63 g O□ /g substance
ThOD	3.1 g O□ /g substance
o-xylene (95-47-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	1.64 g O□ /g substance
Chemical oxygen demand (COD)	2.91 g O□ /g substance
ThOD	3.125 g O□ /g substance
p-xylene (106-42-3)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	1.4 g O□ /g substance
Chemical oxygen demand (COD)	2.56 g O□ /g substance
ThOD	3.125 g O□ /g substance
methanol (67-56-1)	
Persistence and degradability Biochemical oxygen demand (BOD)	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Chemical oxygen demand (COD)	0.6 - 1.12 g O□ /gsubstance 1.42 g O□ /g substance
ThOD	1.5 g O□ /g substance
BOD (% of ThOD)	0.8 (Literature study)
octane (111-65-9)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in so
Biochemical oxygen demand (BOD)	2.33 g $O\Box$ /g substance (35d)
ThOD	3.5 g O /g substance
BOD (% of ThOD)	0.67 (35 days)
3. Bioaccumulative potential	
Custom Low VPH Mix	
Bioaccumulative potential	Not established.
benzene (71-43-2)	
BCF fish 1	19 (BCF)
BCF fish 2	 < 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value)
BCF other aquatic organisms 1	30 (BCF; 24 h; Chlorella sp.)
Log Pow	2.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2 BCF other aquatic organisms 1	15 - 79 (BCF) 4.68 (BCF)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
hexane (110-54-3)	
BCF fish 1	501.187 (BCF; Other; Pimephales promelas)
Log Pow	3.5 - 3.94 (Calculated)
Bioaccumulative potential	Potential for bioaccumulation (500 \leq BCF \leq 5000).
tert-Butyl Methyl Ether (MTBE) (1634-0	14-4)
BCF fish 1	1.5 (BCF; 672 h)
Log Pow	1.06 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
n-pentane (109-66-0)	
BCF fish 1	171 (BCF)
Log Pow	3.45 (Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
styrene (100-42-5)	
BCF fish 1	35.5 (BCF)
Log Pow	2.96 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
toluene (108-88-3)	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1,2,4-trimethylbenzene (95-63-6)	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation ($4 \ge Log$ Kow ≤ 5).
m-xylene (108-38-3)	
BCF fish 1	15 (BCF)
BCF fish 2	24 (BCF)
Log Pow	3.2 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
o-xylene (95-47-6)	
BCF fish 1	21.4 (BCF)
BCF fish 2	14.1 (BCF)
BCF other aquatic organisms 1	219 (BCF)
Log Pow	3.12 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
p-xylene (106-42-3)	
BCF fish 1	15 (BCF)
BCF fish 2	23 (BCF; 240 h)
Log Pow	3.15 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
octane (111-65-9)	
BCF fish 1	776 - 5129 (BCF)
BCF other aquatic organisms 1	198.7 (BCF; 105 minutes; Mytilus edulis; Static system; Salt water; Experimental value)
Log Pow	5.18 (Experimental value)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
4. Mobility in soil	
benzene (71-43-2)	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

benzene (71-43-2)	
Log Koc	Koc,134.1; QSAR
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Log Koc	log Koc, PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
	value
hexane (110-54-3)	
Surface tension	0.018 N/m (25 °C; 1 g/l)
Log Koc	Koc,2187.76; QSAR; log Koc; 3.34; QSAR
tert-Butyl Methyl Ether (MTBE) (1634-04-4)	
Surface tension	0.02 N/m (20 °C)
n-pentane (109-66-0)	
Surface tension	0.015 N/m (25 °C; 100 %; 0.013 N/m; 20 °C)
Log Koc	log Koc,2.9; QSAR
styrene (100-42-5)	
Surface tension	0.032 N/m (19 °C)
Log Koc	Koc,352; Estimated value; log Koc; 2.55; Estimated value
toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
1,2,4-trimethylbenzene (95-63-6) Surface tension	0.020 N/m
	0.029 N/m
Log Koc	log Koc,3.04; Calculated value May be harmful to plant growth, blooming and fruit formation.
Ecology - soil	
m-xylene (108-38-3)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
o-xylene (95-47-6)	
Surface tension	0.003 N/m (25 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
p-xylene (106-42-3)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Кос	Koc,PCKOCWIN v1.66; 1; Calculated value
octane (111-65-9)	
Surface tension	0.022 N/m
Log Koc	Koc,SRC PCKOCWIN v2.0; 436.8; Calculated value; log Koc; SRC PCKOCWIN v2.0; 2.64; Calculated value
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Other adverse effects	
Additional information	: Avoid release to the environment
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / ADN	
14.1. UN number	
	: 1992
UN-No. (IATA)	: 1992
	: 1992
UN-No. (ADN)	: 1992
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, TOXIC, N.O.S.
17/07/2017	EN (English) 11/14

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) v	vith its amendment Regulation (EU) 2015/830
Proper Shipping Name (IATA)	: Flammable liquid, toxic, n.o.s.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, TOXIC, N.O.S.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, TOXIC, N.O.S.
Transport document description (ADR)	: UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S., 3 (6.1), II, (D/E)
14.3. Packing group	
Class (ADR)	: 3
Classification code (ADR)	: FT1
Class (IATA)	: 3
Class (IMDG)	: 3
Class (ADN)	: 3
Classification code (ADN)	: FT1
Subsidiary risk (ADR)	: 6.1
Subsidiary risk (IMDG)	: 6.1
Danger labels (ADR)	: 3, 6.1
Hazard labels (IATA)	: 3, 6.1
Danger labels (IMDG)	: 3, 6.1
Danger labels (ADN)	: 3, 6.1
14.4. Packing group	★ ¥
Packing group (ADR)	: 11
Packing group (IATA) Packing group (IMDG)	
Packing group (ADN)	: " : II
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
14.6.1. Overland transport Hazard identification number (Kemler No.)	: 336
Classification code (ADR)	: 530 : FT1
Orange plates	
Grange places	<u>336</u> 1992
Special provisions (ADR)	: 274
Transport category (ADR)	: 2
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E2
14.6.2. Transport by sea	
Special provisions (IMDG)	: 274
47/07/0047	

EN (English)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) wi	
Limited quantities (IMDG)	: 1L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP2, TP13
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Flammable toxic liquid which is not specified by name in this class or, on account of its characteristics, in some other class. Toxic if swallowed, by skin contact or by inhalation.
14.6.3. Air transport	
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
PCA packing instructions (IATA)	: 352
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA max net quantity (IATA)	: 1L
PCA Excepted quantities (IATA)	: E2
Special provisions (IATA)	: A3
ERG code (IATA)	: 3HP
14.6.4. Inland waterway transport	
Special provisions (ADN)	: 274, 802
Limited quantities (ADN)	: 1L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, TOX, A
Ventilation (ADN)	: VE01, VE02
Number of blue cones/lights (ADN)	: 2
Carriage prohibited (ADN)	: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment ha	as been carried out
SECTION 16: Other inform	nation
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.
PHV SDS EU	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.