

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Custom VOC Standard
Product code : AL0-130031
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Laboratory Use
Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Phenova
6390 Joyce Dr. Suite 100
80403 Golden, CO - United States
T 1-866-942-2978 - F 1-866-283-0269
info@phenova.com - www.phenova.com

1.4. Emergency telephone number

Emergency number : ChemTel Assistance (US/Canada) 1-800-255-3924
ChemTel Assistance (International) +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 1	H224
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Muta. 1B	H340
Carc. 1A	H350
STOT SE 1	H370
Aquatic Chronic 3	H412

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45
Muta.Cat.2; R46
F+; R12
T; R23/24/25
T; R39/23/24/25
R52/53

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS06



GHS08

Custom VOC Standard

Safety Data Sheet

Signal word (CLP)	: Danger
Hazardous ingredients	: benzene; methanol
Hazard statements (CLP)	: H224 - Extremely flammable liquid and vapor H301+H311 - Toxic if swallowed or in contact with skin H340 - May cause genetic defects H350 - May cause cancer H370 - Causes damage to organs H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P260 - Do not breathe dust/fume/gas/mist/vapors/spray P270 - Do not eat, drink or smoke when using this product P273 - Avoid release to the environment P280 - Wear protective gloves/protective clothing/eye protection/face protection P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P308+P313 - IF exposed or concerned: Get medical advice/attention P361+P364 - Take off immediately all contaminated clothing and wash it before reuse P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up

No labeling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methanol (Component)	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	97	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
isopentane (Component)	(CAS No) 78-78-4 (EC no) 201-142-8 (EC index no) 601-006-00-1	0.2	Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
n-pentane (Component)	(CAS No) 109-66-0 (EC no) 203-692-4 (EC index no) 601-006-00-1	0.2	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
benzene (Component)	(CAS No) 71-43-2 (EC no) 200-753-7 (EC index no) 601-020-00-8	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
hexane (Component)	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cyclohexane (Component)	(CAS No) 110-82-7 (EC no) 203-806-2 (EC index no) 601-017-00-1	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
o-xylene (Component) substance with a Community workplace exposure limit	(CAS No) 95-47-6 (EC no) 202-422-2 (EC index no) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
m-xylene (Component) substance with a Community workplace exposure limit	(CAS No) 108-38-3 (EC no) 203-576-3 (EC index no) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315

Custom VOC Standard

Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
p-xylene (Component) substance with a Community workplace exposure limit	(CAS No) 106-42-3 (EC no) 203-396-5 (EC index no) 601-022-00-9	0.2	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
toluene (Component)	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene (Component) substance with a Community workplace exposure limit	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	0.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
heptane (Component)	(CAS No) 142-82-5 (EC no) 205-563-8 (EC index no) 601-008-00-2	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2,4-trimethylpentane (Component)	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	0.2	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
methylcyclohexane (Component)	(CAS No) 108-87-2 (EC no) 203-624-3 (EC index no) 601-018-00-7	0.2	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
octane (Component)	(CAS No) 111-65-9 (EC no) 203-892-1 (EC index no) 601-009-00-8	0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Name	Product identifier	Specific concentration limits	
methanol (Component)	(CAS No) 67-56-1 (EC no) 200-659-6 (EC index no) 603-001-00-X	(3 =<C < 10) STOT SE 2, H371 (C >= 10) STOT SE 1, H370	
hexane (Component)	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	(C >= 5) STOT RE 2, H373	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause cancer by inhalation.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

Custom VOC Standard

Safety Data Sheet

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up in absorbent material. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.
Hygiene measures : Do not eat, drink or smoke when using this product. Gently wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Keep in fireproof place. Keep container tightly closed. Keep container tightly closed and in a well-ventilated place. Keep away from any flames or sparking source.
Incompatible materials : Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

benzene (71-43-2)

USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm

8.2. Exposure controls

- Appropriate engineering controls : Either local exhaust or general room ventilation is usually required.
Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.



- Hand protection : Wear chemically resistant protective gloves. Wear suitable gloves resistant to chemical penetration.
Eye protection : Chemical goggles or safety glasses. Safety glasses.

Custom VOC Standard

Safety Data Sheet

Skin and body protection	: Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless.
Odor	: characteristic.
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable liquid and vapor
Relative density	: No data available
Solubility	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Sparks. Heat. Overheating. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin.

Custom VOC Standard

ATE CLP (oral)	103.093 mg/kg body weight
ATE CLP (dermal)	309.278 mg/kg body weight

isopentane (78-78-4)

LD50 oral rat	> 5000 mg/kg (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 25.3 mg/l/4h (Rat; Read-across)

n-pentane (109-66-0)

LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
---------------	---

hexane (110-54-3)

LD50 oral rat	16000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3350 mg/kg body weight (Rabbit; Read-across; Equivalent or similar to OECD 402)
ATE CLP (oral)	16000.000 mg/kg body weight

Custom VOC Standard

Safety Data Sheet

cyclohexane (110-82-7)	
LD50 oral rat	> 12705 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; >5000 mg/kg bodyweight; Rat)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 19.07 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	> 5540 ppm/4h (Rat)
benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
ATE CLP (gases)	13700.000 ppmV/4h
ATE CLP (vapors)	43.767 mg/l/4h
ATE CLP (dust, mist)	43.767 mg/l/4h
2,2,4-trimethylpentane (540-84-1)	
LD50 oral rat	> 5000 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (Rat; Experimental value)
heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
ATE CLP (gases)	25000.000 ppmV/4h
ATE CLP (vapors)	103.000 mg/l/4h
ATE CLP (dust, mist)	103.000 mg/l/4h
methylcyclohexane (108-87-2)	
LD50 oral rat	> 5840 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Read-across)
LD50 dermal rat	> 2800 mg/kg body weight (Rat; Read-across)
LD50 dermal rabbit	86700 mg/kg (Rabbit; Literature study)
toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat; Literature study)
ATE CLP (dermal)	12223.000 mg/kg body weight
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	3500.000 mg/kg body weight
ATE CLP (dermal)	15415.000 mg/kg body weight
ATE CLP (gases)	4000.000 ppmV/4h
ATE CLP (vapors)	17.800 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
m-xylene (108-38-3)	
LD50 oral rat	5011 - 6630 mg/kg (Rat)
ATE CLP (oral)	5011.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
p-xylene (106-42-3)	
LD50 oral rat	4030 mg/kg (Rat)
LC50 inhalation rat (mg/l)	20 mg/l/4h (Rat)

Custom VOC Standard

Safety Data Sheet

p-xylene (106-42-3)	
LC50 inhalation rat (ppm)	4740 ppm/4h (Rat)
ATE CLP (oral)	4030.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4740.000 ppmV/4h
ATE CLP (vapors)	20.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
o-xylene (95-47-6)	
LD50 oral rat	3608 mg/kg (Rat)
ATE CLP (oral)	3608.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
octane (111-65-9)	
LD50 oral rat	5630 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Read-across; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	118 mg/l/4h (Rat; Literature study)
ATE CLP (oral)	5630.000 mg/kg body weight
ATE CLP (vapors)	118.000 mg/l/4h
ATE CLP (dust, mist)	118.000 mg/l/4h
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15800 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (gases)	700.000 ppmV/4h
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	0.500 mg/l/4h

Skin corrosion/irritation	: Not classified Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer. May cause cancer
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Causes damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

isopentane (78-78-4)	
LC50 fish 1	3.1 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	2.3 mg/l (EC50; 48 h)
Threshold limit algae 2	2.620 mg/l (EC50; 72 h; Algae)

Custom VOC Standard

Safety Data Sheet

hexane (110-54-3)	
LC50 fish 1	2.5 mg/l (LC50; 96 h)
EC50 Daphnia 1	2.1 mg/l (EC50; 48 h)
Threshold limit algae 2	26 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system)
cyclohexane (110-82-7)	
LC50 fish 1	4.53 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	0.9 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	3.428 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
Threshold limit algae 2	0.925 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum)
benzene (71-43-2)	
LC50 fish 1	5.3 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 2	10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
Threshold limit algae 1	100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
2,2,4-trimethylpentane (540-84-1)	
EC50 Daphnia 1	0.4 mg/l (EC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Read-across)
Threshold limit algae 1	2.943 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Fresh water)
heptane (142-82-5)	
EC50 Daphnia 1	0.2 mg/l (LC50; Other; 96 h; Chaetogammarus marinus; Semi-static system; Salt water; Experimental value)
methylcyclohexane (108-87-2)	
LC50 fish 2	5.4 mg/l (LC50; 96 h; Salmo gairdneri; Semi-static system)
Threshold limit algae 2	29 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Read-across)
ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)
m-xylene (108-38-3)	
EC50 Daphnia 1	4.7 mg/l (EC50; 48 h)
LC50 fish 2	8.4 mg/l (LC50; 96 h)
p-xylene (106-42-3)	
LC50 fish 1	2.6 mg/l (LC50; 96 h)
EC50 Daphnia 2	1.4 mg/l (EC50; 48 h)
o-xylene (95-47-6)	
EC50 other aquatic organisms 1	4.7 mg/l (72 h; Selenastrum capricornutum; Growth)
LC50 fish 2	8.05 mg/l (LC50; 96 h)
EC50 Daphnia 2	3.2 mg/l (EC50; 48 h)
octane (111-65-9)	
EC50 Daphnia 1	0.38 mg/l (EC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

Custom VOC Standard	
Persistence and degradability	May cause long-term adverse effects in the environment.
isopentane (78-78-4)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Adsorbs into the soil. Photodegradation in the air.
ThOD	3.55 g O ₂ /g substance
n-pentane (109-66-0)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil.

Custom VOC Standard

Safety Data Sheet

hexane (110-54-3)	
Persistence and degradability	Readily biodegradable in water. Photooxidation in water. easily degradable in the soil.
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	0.63 (Literature study)
cyclohexane (110-82-7)	
Persistence and degradability	Readily biodegradable in water. Non degradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O ₂ /g substance
BOD (% of ThOD)	< 0.5 (Literature study)
benzene (71-43-2)	
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	2.18 g O ₂ /g substance
Chemical oxygen demand (COD)	2.15 g O ₂ /g substance
ThOD	3.10 g O ₂ /g substance
BOD (% of ThOD)	0.70
2,2,4-trimethylpentane (540-84-1)	
Persistence and degradability	Not readily biodegradable in water. Non degradable in the soil.
ThOD	3.50 g O ₂ /g substance
heptane (142-82-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	0.06 g O ₂ /g substance
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	> 0.5 (5 days; Literature study)
methylcyclohexane (108-87-2)	
Persistence and degradability	Not readily biodegradable in water. Low potential for adsorption in soil.
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)
m-xylene (108-38-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air. Photooxidation in the air.
Biochemical oxygen demand (BOD)	2.53 g O ₂ /g substance
Chemical oxygen demand (COD)	2.63 g O ₂ /g substance
ThOD	3.1 g O ₂ /g substance
p-xylene (106-42-3)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	1.40 g O ₂ /g substance
Chemical oxygen demand (COD)	2.56 g O ₂ /g substance
ThOD	3.125 g O ₂ /g substance
o-xylene (95-47-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	1.64 g O ₂ /g substance
Chemical oxygen demand (COD)	2.91 g O ₂ /g substance
ThOD	3.125 g O ₂ /g substance
octane (111-65-9)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.

Custom VOC Standard

Safety Data Sheet

octane (111-65-9)	
Biochemical oxygen demand (BOD)	2.33 g O ₂ /g substance (35d)
ThOD	3.50 g O ₂ /g substance
BOD (% of ThOD)	0.67 (35 days)
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)
12.3. Bioaccumulative potential	
Custom VOC Standard	
Bioaccumulative potential	Not established.
isopentane (78-78-4)	
BCF fish 1	136 (BCF)
Log Pow	3.4 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
n-pentane (109-66-0)	
BCF fish 1	171 (BCF)
Log Pow	3.45 (Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
hexane (110-54-3)	
BCF fish 1	501.187 (BCF; Other; Pimephales promelas)
Log Pow	3.5 - 3.94 (Calculated)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
cyclohexane (110-82-7)	
BCF fish 2	31 - 129 (BCF; 8 weeks; Cyprinus carpio)
Log Pow	3.44 (Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
benzene (71-43-2)	
BCF fish 1	19 (BCF)
BCF fish 2	< 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value)
BCF other aquatic organisms 1	30 (BCF; 24 h; Chlorella sp.)
Log Pow	2.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2,2,4-trimethylpentane (540-84-1)	
BCF fish 2	231 (BCF)
Log Pow	4.08 - 5.18 (Calculated; KOWWIN)
heptane (142-82-5)	
BCF other aquatic organisms 1	552 (BCF; BCFBAF v3.00)
Log Pow	4.66 (Experimental value; 4.5; Literature study)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
methylcyclohexane (108-87-2)	
BCF fish 1	95 - 321 (BCF; 8 weeks; Cyprinus carpio)
Log Pow	3.88 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
toluene (108-88-3)	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Custom VOC Standard

Safety Data Sheet

m-xylene (108-38-3)	
BCF fish 1	15 (BCF)
BCF fish 2	24 (BCF)
Log Pow	3.20 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
p-xylene (106-42-3)	
BCF fish 1	15 (BCF)
BCF fish 2	23 (BCF; 240 h)
Log Pow	3.15 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
o-xylene (95-47-6)	
BCF fish 1	21.4 (BCF)
BCF fish 2	14.1 (BCF)
BCF other aquatic organisms 1	219 (BCF)
Log Pow	3.12 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
octane (111-65-9)	
BCF fish 1	776 - 5129 (BCF)
BCF other aquatic organisms 1	198.7 (BCF; 105 minutes; Mytilus edulis; Static system; Salt water; Experimental value)
Log Pow	5.18 (Experimental value)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
methanol (67-56-1)	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
isopentane (78-78-4)	
Surface tension	0.01549 N/m (25 °C; 100 vol %)
n-pentane (109-66-0)	
Surface tension	0.015 N/m (25 °C; 100 %; 0.013 N/m; 20 °C)
Log Koc	log Koc,2.9; QSAR
hexane (110-54-3)	
Surface tension	0.018 N/m (25 °C; 1 g/l)
Log Koc	Koc,2187.76; QSAR; log Koc; 3.34; QSAR
cyclohexane (110-82-7)	
Surface tension	0.025 N/m (20 °C)
Log Koc	log Koc,Other; 2.89; QSAR; Koc; Other; 770; QSAR
benzene (71-43-2)	
Surface tension	0.029 N/m (20 °C)
Log Koc	Koc,134.1; QSAR
2,2,4-trimethylpentane (540-84-1)	
Log Koc	log Koc,SRC PCKOCWIN v2.0; 2.58; Calculated value; Koc; SRC PCKOCWIN v2.0; 240.3; Calculated value
heptane (142-82-5)	
Surface tension	0.019 N/m (25 °C; 0.020 N/m; 20 °C)
Log Koc	log Koc,SRC PCKOCWIN v2.0; 2.38; Calculated value
methylcyclohexane (108-87-2)	
Log Koc	log Koc,SRC PCKOCWIN v2.0; 2.369; Calculated value
toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
m-xylene (108-38-3)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

Custom VOC Standard

Safety Data Sheet

p-xylene (106-42-3)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
o-xylene (95-47-6)	
Surface tension	0.003 N/m (25 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
octane (111-65-9)	
Surface tension	0.022 N/m
Log Koc	Koc, SRC PCKOCWIN v2.0; 436.8; Calculated value; log Koc; SRC PCKOCWIN v2.0; 2.64; Calculated value
methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc, PCKOCWIN v1.66; 1; Calculated value

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1992
UN-No.(IATA) : 1992

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, TOXIC, N.O.S.
Proper Shipping Name (IATA) : FLAMMABLE LIQUID, TOXIC, N.O.S.
Transport document description (ADR) : UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (FLAMMABLE LIQUID, TOXIC, N.O.S.), 3 (6.1), II, (D/E)

14.3. Packing group

Class (ADR) : 3
Classification code (ADR) : FT1
Class (IATA) : 3
Subsidiary risks (ADR) : 6.1
Hazard labels (ADR) : 3, 6.1



Hazard labels (IATA) : 3, 6.1



14.4. Packing group

Packing group (ADR) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 336

Custom VOC Standard

Safety Data Sheet

Classification code (ADR) : FT1
Orange plates :



Special provision (ADR) : 274
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E2

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
PCA packing instructions (IATA) : 352
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA max net quantity (IATA) : 1L
PCA Excepted quantities (IATA) : E2
ERG code (IATA) : 3HP

14.6.4. Inland waterway transport

Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Contains no REACH candidate substance
Contains no REACH Annex XIV substances.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

PHV SDS EU

Copyright 2015 Phenova, Inc. License granted to make paper copies for internal use. The information contained in this Safety Data Sheet is based on our current knowledge. The information contained in this document should be used only as a guide for appropriate safety precautions and should not be considered to be all inclusive. Users should make their own investigation to determine the suitability of the information for their particular purposes. The document does not represent any guarantee of the properties of the product. Phenova, Inc. shall not be held liable for any damage resulting from the handling or use of this product. Visit the Terms and Conditions of Sale link at www.phenova.com for additional terms and conditions of sale.