

APPLICATIONS

Comparison of Fully Porous and Superficially Porous Particles for the Analysis of Synthetic Oligonucleotides

Dr. Ivan Lebedev¹, Brian Rivera¹, and Dr. Helen Whitby²

¹Phenomenex, Inc., 411 Madrid Ave., Torrance, CA 90501 USA

²Phenomenex LTD, Queens Avenue, Hurdsfield Ind. Est., Macclesfield, Cheshire SK10 2BN, UK

Overview

Superficially porous particle technologies provide a reduced diffusion path in comparison with their fully porous counterparts reducing the resistance to mass transfer during chromatographic separation. With these particles, one can benefit from their greater efficiency either through improved separation or achieving comparable efficiency with a larger particle size. This enables the method flexibility to increase flow rate. When this is coupled with the benefits of bio-inert hardware, a greater level of separation of oligonucleotide impurities can be observed compared to a sub-2µm fully porous hybrid silica. The potential to implement a faster flow rate offers the opportunity for shorter analysis times or increased sample throughput; further lower backpressure can contribute to improved column lifetime especially considering the harsh conditions associated to oligo analysis by ion-pairing reversed phase LC. In this application note, we compare the performance of two different particle size core-shell columns (bioZen™ Oligo 2.6 µm and 1.7 µm) with their fully porous alternatives.

With the 2.6 µm bioZen Oligo, we clearly see an improvement in sensitivity over a 2.5 µm fully porous column using the high efficiency core-shell material. Figure 1 demonstrates the narrower peaks and a greater sensitivity achieved for a 5'-Amino C12 oligo when run using the 2.6 µm bioZen Oligo. This reduction in peak width afforded better resolution and definition of the impurity peaks to be achieved.

In Figure 2 we compare the separation of a ssDNA using the 1.7 µm bioZen oligo. Using a sub-2 µm core-shell particle, greater level of detail in the impurity profile is observed with when compared to the 1.7 µm fully porous alternative in the same dimensions. For both chemistries running the method at a flow rate slightly higher than is typical (0.5 mL/min) gave better results. It was noted for longer oligonucleotides like the 33mer analyzed here, recovery of shorter impurities is improved with bioZen Oligo, likely a result of the inert bio-inert hardware.

Figure 3 highlights the potential benefits of the high efficiency of a core shell particle at higher flow. The bioZen oligo 2.6 µm when used to analyze an RNA 21mer achieved comparable performance to the 1.7 µm fully porous column however running a significantly lower backpressure. This reduction in backpressure is likely, overtime contribute favorably to improved column lifetime for the 2.6 µm particle compared with sub-2 µm alternatives.

LC Conditions (Figure 1)

Column:	bioZen 2.6 µm Oligo Fully Porous 2.5 µm C18
Dimensions:	50 x 2.1 mm
Mobile Phase A :	10 mM HA in Water; 12.5 mM HFIP
Mobile Phase B:	10 mM HA in MeOH; 12.5 mM HFIP
Gradient:	25-75 % B, 14 minutes
Detection:	UV @ 260 nm
Flow Rate:	0.5 mL/min
Temperature:	65 °C

LC Conditions (Figure 2)

Column:	bioZen 1.7 µm Oligo Fully Porous 1.7 µm C18
Dimensions:	50 x 2.1 mm
Mobile Phase A :	10 mM HA in Water; 12.5 mM HFIP
Mobile Phase B:	10 mM HA in MeOH; 12.5 mM HFIP
Gradient:	25-75 % B, 14 minutes
Detection:	UV @ 260 nm
Flow Rate:	0.5 mL/min
Temperature:	65 °C

LC Conditions (Figure 3)

Column:	bioZen 2.6 µm Oligo Brand A 1.7 µm C18
Dimensions:	50 x 2.1 mm
Mobile Phase A :	10mM HA in Water; 12.5mM HFIP
Mobile Phase B:	10mM HA in MeOH; 12.5mM HFIP
Gradient:	25-75% B, 14 minutes
Detection:	UV@260nm
Flow Rate:	0.5 mL/min
Temperature:	65 °C

Figure 1. bioZen™ Oligo 2.6µm vs Fully Porous 2.5 µm C18 for a 5'-Amino C12




Figure 2. bioZen Oligo 1.7 µm vs Fully Porous 2.5 µm C18 for a ss 33mer.





Figure 3. Comparative data for bioZen Oligo 2.6 µm vs Brand A 1.7µm for a ssRNA 21 mer



APPLICATIONS

Need a different column size or sample preparation format?

No problem! We have a majority of our available dimensions up on www.phenomenex.com, but if you can't find what you need right away, our super helpful Technical Specialists can guide you to the solution via our online chat portal www.phenomenex.com/LiveChat.

Australia

t: +61 (0)2-9428-6444
auinfo@phenomenex.com

Austria

t: +43 (0)1-319-1301
anfrage@phenomenex.com

Belgium

t: +32 (0)2 503 4015 (French)
t: +32 (0)2 511 8666 (Dutch)
beinfo@phenomenex.com

Canada

t: +1 (800) 543-3681
info@phenomenex.com

China

t: +86 400-606-8099
cninfo@phenomenex.com

Denmark

t: +45 4824 8048
nordicinfo@phenomenex.com

Finland

t: +358 (0)9 4789 0063
nordicinfo@phenomenex.com

France

t: +33 (0)1 30 09 21 10
franceinfo@phenomenex.com

Germany

t: +49 (0)6021-58830-0
anfrage@phenomenex.com

India

t: +91 (0)40-3012 2400
indiainfo@phenomenex.com

Ireland

t: +353 (0)1 247 5405
eirinfo@phenomenex.com

Italy

t: +39 051 6327511
italiainfo@phenomenex.com

Luxembourg

t: +31 (0)30-2418700
nlinfo@phenomenex.com

Mexico

t: 01-800-844-5226
tecnicomx@phenomenex.com

The Netherlands

t: +31 (0)30-2418700
nlinfo@phenomenex.com

New Zealand

t: +64 (0)9-4780951
nzinfo@phenomenex.com

Norway

t: +47 810 02 005
nordicinfo@phenomenex.com

Portugal

t: +351 221 450 488
ptinfo@phenomenex.com

Singapore

t: +65 800-852-3944
sginfo@phenomenex.com

Spain

t: +34 91-413-8613
esinfo@phenomenex.com

Sweden

t: +46 (0)8 611 6950
nordicinfo@phenomenex.com

Switzerland

t: +41 (0)61 892 20 20
swissinfo@phenomenex.com

United Kingdom

t: +44 (0)1625-501367
ukinfo@phenomenex.com

USA

t: +1 (310) 212-0555
info@phenomenex.com

🌐 **All other countries/regions**
Corporate Office USA
t: +1 (310) 212-0555
info@phenomenex.com

www.phenomenex.com

Phenomenex products are available worldwide. For the distributor in your country, contact Phenomenex USA, International Department at international@phenomenex.com